



# Premier PH200NS

## Homopolymer Polypropylene

**MELT FLOW: 20.0**

**DENSITY: 0.9**

**Premier PH200NS** is a nucleated polypropylene homopolymer intended for injection molding applications, and contains an anti-static additive.

<u>Resin Property</u>	<u>Typical Value</u>	<u>Units</u>	<u>Test Method</u>
Melt Flow Rate, I <sub>2</sub> @ 230 °C	20.0	g/10 min	ASTM D-1238
Density	0.9	g/cm <sup>3</sup>	ASTM D-1505
Tensile Strength at Yield (50 mm/min)	5000	Psi	ASTM D-638
Flexural Modulus (1.3 mm/min), 1% Secant	180,000	psi	ASTM D-790
Elongation at Yield (50 mm/min)	8	%	ASTM D-638
Notched Izod Impact Strength @ 73°F	.4	Ft-lb/in	ASTM D-256

Premier Polymers cannot anticipate or control the many different conditions under which this information and/or product may be used. It does not guarantee the applicability or the accuracy of this information or the suitability of its products in any given situation. User of the material should make their own tests to determine the suitability of each such product for their particular purposes. The data listed herein falls within the normal range of product properties but they should not be used to establish specification limits or used alone as the basis of design.

Premier Polymers, LLC. 16800 Imperial Valley Drive, Suite 400 Houston, TX 77060  
Phone: 281-902-0900 Fax: 281-260-8096