



# Premier PI210

## Impact Copolymer Polypropylene

**MELT FLOW: 20.0**

**DENSITY: 0.90**

**Premier PI210** is an impact copolymer polypropylene with high ethylene content and designed for injection molding applications and as a base resin for compounding. It has good impact performance and high tensile strength. Targeted applications include industrial supplies, as well as a base resin for automotive compounds. This resin has \*FDA compliance.

<u>Resin Property</u>	<u>Typical Value</u>	<u>Units</u>	<u>Test Method</u>
Melt Flow	20.0	g/10 min	ASTM D-1238
Density	0.90	g/cm <sup>3</sup>	ASTM D-792
Tensile Strength at Yield	3,840 (26)	psi (MPa)	ASTM D-638
Elongation at Break	>100	%	ASTM D-638
Flexural Modulus	185,000 (1,280)	psi (MPa)	ASTM D-790
Heat Deflection Temp. (4.6 kgf/cm <sup>2</sup> )	105	Deg. C	ASTM D-648
Notched Izod Impact (23C)	1.3 (69)	ft-lbs/in (J/m)	ASTM D-256
Notched Izod Impact (-10C)	0.74 (39)	ft-lbs/in (J/m)	ASTM D-256

Premier Polymers cannot anticipate or control the many different conditions under which this information and/or product may be used. It does not guarantee the applicability or the accuracy of this information or the suitability of its products in any given situation. User of the material should make their own tests to determine the suitability of each such product for their particular purposes. The data listed herein falls within the normal range of product properties but they should not be used to establish specification limits or used alone as the basis of design.

\*21 CFR 177.1520 (C)

Premier Polymers, LLC. 16800 Imperial Valley Drive, Suite 400 Houston, TX 77060  
Phone: 281-902-0900 Fax: 281-260-8096