



Premier PI210K

Impact Copolymer Polypropylene

MELT FLOW: 20.0

DENSITY: 0.895

Premier PI210K is a heterophasic impact copolymer polypropylene with high melt flow and impact strength. This resin is suitable for applications requiring high mechanical properties.

<u>Resin Property</u>	<u>Typical Value</u>	<u>Units</u>	<u>Test Method</u>
Melt Flow	20.0	g/10 min	ASTM D-1238
Density	0.895	g/cm ³	ASTM D-792
Tensile Elongation at Yield	6.0	%	ASTM D-638
Flexural Modulus (1% Secant, Inj. Molded)	109,000	psi	ASTM D-790
Flexural Modulus (Inj. Molded)	94,300	psi	ISO 178
Hardness, Rockwell	46	R Scale	ASTM D-785
Notched Izod Impact (23° C)	No Break	ft-lb/in	ASTM D-256
Notched Izod Impact (-20° C)	1.87	ft-lb/in	ASTM D-256

Premier Polymers cannot anticipate or control the many different conditions under which this information and/or product may be used. It does not guarantee the applicability or the accuracy of this information or the suitability of its products in any given situation. User of the material should make their own tests to determine the suitability of each such product for their particular purposes. The data listed herein falls within the normal range of product properties but they should not be used to establish specification limits or used alone as the basis of design.

Premier Polymers, LLC. 16800 Imperial Valley Drive, Suite 400 Houston, TX 77060
Phone: 281-902-0900 Fax: 281-260-8096